

Solar Charge Controller 30A auto 12/24V



- Rated Current: 30A
- Rated Voltage: 12V/24V (Auto Switch)
- Maximum Voltage of solar panel: 50V
- Float Voltage: 13.7V/27.4V
- Low Voltage Disconnection: 10.7V/21.4V
- Low Voltage Reconnection: 12.6V/25.2V
- Max Power: 1440W:24V , 720W:12V
- Battery Type: Lead-acid,GEL,Flooded
- No load loss: <30mA
- loop voltage drop: <200mV
- Charging Mode: PWM Mode
- Temperature Compensation: -4mV/Cell/Degree

Features:

CM series controller is a kind of intelligent and multifunctional solar charge controller. These serial products adopt customized LCD display screen, which makes the operation on the interface rather convenient. All the controlling parameters can be reset flexibly to satisfy your different needs. CM series controller has the following features.

- Visual LCD graphic symbol
- Brief key operation
- Grade auto switch of system voltage
- Intelligent PWM Charging Mode
- Auto temperature compensation
- Adjustable charging & discharging parameter
- Settable working modes of loads
- Accumulative function of charging & discharging AH
- Protection for battery back discharging
- Protection for battery low voltage
- Overloading & short-circuit protection
- Battery reversed protection
- Delayed auto restart after overloading protection
- CE & RoHS Certification

รับประกันสินค้า 6 เดือน